

KEY HIGHLIGHTS



Premium Lithium Iron Phosphate (LiFePO₄) technology.



Modular design for effortless capacity expansion.



Ultra-long cycle life for decade-plus reliability.



Prioritize your solar harvest.



**“Scaleable.
Sustainable.
Secure.”**

CONTACT US TODAY!



+92 51 843 2273



info@norasol.net



www.norasol.net



Plot 424, I-9/3 Islamabad,
Pakistan



Scan to explore our latest eco-friendly listings.



NoraSol

NORASTORE-5
EMPOWER YOUR ENERGY
INDEPENDENCE.

HIGH-PERFORMANCE 5.12 KWH
LIFEPO₄ BATTERY STORAGE
SYSTEM.

RELIABILITY
YOU CAN
TRUST.

5 Years
Warranty

ADVANCED BMS INTELLIGENCE

- Integrated Intelligent Battery Management System (BMS) monitors voltage, current, and temperature at the cell level.
- Active cell balancing extends battery health and maximizes usable energy.
- Dual RS485 and CAN ports for seamless integration with leading hybrid inverters.
- Expansion: Dip-switch addressing supports connecting up to 16 units in parallel for massive storage needs.

MODULAR ENERGY STORAGE

- The NoraStore-5 Advantage: A high-density energy solution designed to bridge the gap between solar production and nighttime consumption.
- Scalability: Start with 5.12 kWh and scale up to 81.92 kWh as your energy needs grow.
- Key Applications:
 - Residential Backup: Keep the lights on during grid failures.
 - Peak Shaving: Reduce electricity bills by using stored energy during peak hours.
 - Off-Grid Living: Reliable power for remote locations.

Feature	Specification
Model	NoraStore-5 (ZP-512K)
Nominal Energy	5.12 kWh
Nominal Voltage	51.2 V
Standard Capacity	100 Ah
Recommended Charge/Discharge	50 A (0.5C)
Max Charge/Discharge	100 A (1.0C)
Operating Voltage Range	44.8 V – 57.6 V
Cycle Life	≥ 6,000 Cycles @ 25°C

POWER
WITHOUT
COMPROMISE

SAFETY FIRST

- LiFePO₄ Chemistry: The safest lithium technology, inherently stable and non-combustible.
- Multi-Layer Protection: Over-charge, over-discharge, over-current, and short-circuit protection.

RUGGED CONSTRUCTION

- Installation: Flexible wall-mount or floor-stack configurations.
- Environment: Wide operating temperature range (-10°C to 50°C).
- Protection: Robust enclosure designed for long-term indoor durability.

SUPPORT

Expert local assistance for installation and configuration.

SERVICE LIFE

Designed for 10+ years of operation.